Products - SPACE - Direct/Frame Fix Doors

This doors combines strength, good looks and security. The design includes a contemporary Euro-groove surface mounted multi-point locking system with top and bottom hooks.

The shuffle glazed internal bead design allows for ease of both glazing and deglazing without the need to dismantle the door. Three hinges are fully adjustable in six directions.

Features

1. Choice of Frame Fix or Direct Fix
2. Non-handed and fully reversible
3. 75mm Direct fix compatible with space direct fix window suit
4. Unique fixings without the need of trims
5. Adjustable loc keeps
6. Slimline attractive appearance
7. Ease of fabrication and installation
8. Compatible with all window ancillaries
9. Single and double door configuration
10. Wrap-around design also available

Technical Details

Materials
Extruded aluminium alloy 6063 T6 to BS 1474, 1987
Gaskets are manufactured to BS 7412

Finishes
Mill Finish is available.
Polyester powder coating is to BS 6496, 1984 to the full RAL range available.
Etched and anodised to BS 3987, 1974 and BS 1615, 1987.
Anodised finishes are subject to special order instructions.

Profile Width
45mm (Frame Fix) and 75mm (Direct Fix)

Building Applications
Designed for use as direct fix or sub frame fix, single or double doors for domestic and commercial applications.

Special Features
Opening vents are weather sealed around their perimeter with a high quality silicone treated woven polypropylene pile. High performance TPR bubble seal gasket is also available for high rise and other installations requiring performance in excess of normal severe requirements.

Size Limitations:
Subframe fix : Single - 917mm x 2157mm
Double - 1782mm x 2157mm
Direct fix : Single - 951mm x 2175mm
Double - 1816mm x 2175mm

Glazing
All glazing should be carried out to a recommendations of BS 6262.

Double glazing, 24/24.8mm may be fitted to this door system. The door may be shuffle glazed for site glazing or wrap round glazed. For additional security, the external gasket is captive and the internal gasket a wedge.

Performance
Tested in accordance with:
BS 5368: Part 1:1976 EN42
BS 5368: Part 2:1980 EN86
BS 5368: Part 3:1978 EN77
BS 6375: Part 1:1989
Complies with BS 4873 : 1986